

FITTING & MEASUREMENTS:

The key measurement to focus on is the exact size of your structural opening.

For the best fit, the opening should be 5mm larger on all sides than the sliding door size you are ordering.

For example, if you order a door that's 2100mm(h) by 4000mm(w) , your structural opening should be 2110mm (h) by 4010mm (w) to ensure a smooth fit.

This slight difference allows the doors to be installed smoothly and securely.

We advise each project has its own specifications. If this is a new build, then laminate glass is required to comply with document "L". There may also be a requirement for trickle vents to be incorporated into your project. We advise checking this before purchase as all orders are made to order and sizes/specifications cannot be changed once manufacturing commences. Please note orders for laminate glass are not available on the website, please contact us if you require laminate glass.

SPECIFICATION:

Dimensions

- Frame depths : 120mm double track / 185mm triple track
- Sash depth : 50mm
- Interlock Width : 47mm
- Glazing : 28mm double or 36mm triple glazed units
- Max frame width : 6400mm
- Max frame height* : 2578mm
- Max sash height : 2500mm
- Max sash width 2500mm
- Max glass unit weight: 250Kg

Glazing:

28mm Double Glaze

TOUGHENED UNITS

4mm - 20mm Spacer – 4mm inner Max 2.5m²

6mm - 16mm Spacer – 6mm inner Max 4.5m²

LAMINATED UNITS

4mm - 18mm Spacer – 6.8mm inner Max 2.5m²

6mm - 16mm Spacer – 6.8mm inner Max 4.5m²

36mm Triple Glaze Units (AVAILABLE UPON REQUEST PRICED ON APPLICATION)

TOUGHENED UNITS

4mm – 12mm Spacer – 4mm – 12mm Spacer - 4mm Max 2.94m²

6mm – 10mm Spacer – 6mm – 8mm Spacer - 6mm Max 2.94m²